

PERFORMANCE PLUS CELLULOSE PHENOLIC CARTRIDGES

CARTRIDGES RATED UP TO 250°F

Cellulose Phenolic pleated cartridges for high capacity, high temperature petroleum-based fluid applications.

High flow capability

Lower overall operating cost

Longer filter runs for fewer change outs

Increased contaminate removal

High temperature rating of up to 250°F (121°C)

FEATURES

- Fewer cartridges for fewer change outs and lower maintenance cost
- Pleated filter media provides higher flow rates and lower initial pressure drop
- Pleated surface area provides higher loading capacity for longer filter life and increased particle removal
- Petroleum-based fluid applications oil based fluid applications
- High surface area in a single cartridge design
- Made in USA

FITS

- Fits LAKOS models LP, LQ, and CFH Housings



Cellulose Phenolic
10, 20, and 30

APPLICATIONS

Petrochemical
Lubricating Oil

Cutting Fluids
Solvents

Distillate Fuel
Fuel Oil

Hydraulic Fluids
Bio Fuels

PERFORMANCE PLUS CELLULOSE PHENOLIC CARTRIDGES

SPECIFICATIONS

Filter media: cellulose phenolic
 End Caps: powder coated metal
 Temperature: up to 250°F (121°C)

Center Core: powder coated perforated metal
 pH: 6.5 to 9.5

Change Out: 35 PSI ΔP (1.7 bar)
 O-Rings & Sealing Grommet: Buna N standard, optional Viton available

	PRODUCT CODE	Nominal Micron Rating	Media (sq ft)	Recommended Flow Rate* (GPM)	Length (in)	No./Carton
Cellulose Phenolic rated up to 250°F (121°C)						
9 ⁵ / ₈ "	LC-PH-10-5/HT250	5	40	35	9-5/8	1
19 ¹ / ₂ "	LC-PH-20-5/HT250	5	90	70	19-1/2	1
30 ³ / ₄ "	LC-PH-30-5/HT250	5	170	105	30-3/4	1

LAKOS warrants its line of Performance Plus Filters to be free of defects in material and workmanship for a period of one year from the date of installation. See lakos.com/warranty for more information.



Note: This publication is to be used as a guide. The data within has been obtained from many sources and is considered to be accurate. Lakos does not assume liability for the accuracy and/or completeness of this data. Changes to the data can be made without notification. Temperature, Pressure, Flow Rates, Differential Pressures, Chemical Combinations and other unknown factors can affect performance in unknown ways. Limited Warranty: Lakos warrants their products to be free of material and workmanship defects. Determination of suitability of Lakos products for uses and applications contemplated by Buyer shall be the sole responsibility of Buyer. The end user/installer/buyer shall be liable for the product's performance and suitability regarding their specific intended applications. End users should perform their own tests to determine suitability for each application.