

Electric Fail-Safe Valve

Automatically Closes Purge Valve in Case of Power Failure



EFS Valve shown with
purge controller

Specifications:

Voltage: 12V DC, 24V DC and 100-240V AC

Frequency: 50/60Hz

Power Draw: 30-48 VA

Current Draw: 0.3-0.2 A

75% Duty Rated

Valve Open-Close Time: 8 seconds from 0 to 90 degrees.

Fail-Safe Delay: EFS Valve starts closing 5 seconds after power loss

Housing: V0 self-extinguish class techno-polymer, water-tight

Protection Level: NEMA 4/4X IP65 IP67

Certifications: CE UL

Cover Type: UL 50

Ambient Temperature Range: -4 F to 131 F

Auxiliary Contact Rating: 1A @ 30VDC/250VAC RESISTIVE

Protection Against Electrical Shock: Class I

Cover Type: UL 50

Recommended Battery Check: Once per year

Fail-Safe Batteries: Rechargeable Nickel-Metal-Hydride battery pack that provides 400 charge/discharge cycles. The batteries are automatically charged when the supply is connected, expected life span is 10 years.

Models:

Models	Valve Diameter	
	inches	mm
EFS-07	3/4"	19.05
EFS-15	1-1/2"	38.1
EFS-20	2"	50.8


Purge controller is required and included as part of valve kit.

EFS Features and Benefits:

- EFS closes purge valve in case of power failure
- Purges solids automatically – eliminating manual purging
- Visual indicator on EFS provides easy-to-read current valve position
- Manual override for quick purge situations
- EFS features an electronic circuit that adjusts motor speed to keep cycle time constant, maintaining consistent purge durations
- Can be installed in combination with Solids Recovery Vessel (SRV-816 or SRV-833) for short-term conditions that require direct purging
- Actuator housing made of V0 self-extinguish material for fire safety
- EFS features a torque limiter circuit that protects motor from overcurrent or overtorque conditions

EFS Installation:

SEPARATOR OUTLET



EFS and LAKOS Controller automatically purge separated solids from Separator's collection chamber at pre-determined time intervals – eliminating manual purging.

Contact LAKOS for EFS installation guide with more detailed specifications.

LAKOS® is a trademark of LAKOS Corporation

LAKOS is a proud and contributing member of ASHRAE for over 30 years

LS-913D (Rev. 6/22)



1365 N. Clovis Avenue • Fresno, California 93727 USA
Telephone: (559) 255-1601
www.lakos.com • info@lakos.com