		0	
	EXCEPT AS OTHERWISE PROVIDED BY CONTRACT, THIS DRAWING AND SPECIFICATIONS SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR MANUFACTURE OR SALE OF MATTER DEPICTED HEREIN WITHOUT THE EXPRESSED WRITTEN PERMISSION OF THE LAKOS CORPORATION, OR ITS ASSIGNEES.		Ψ
	NOTES:	Ø 1/2"[13] TYP	/8"[35] TYP
D	<ol> <li>INLET IS 4" PIPE (GROOVED).</li> <li>OUTLET IS 3" PIPE (GROOVED).</li> <li>PURGE OUTLET IS 3/4" NPT.</li> <li>MAXIMUM PRESSURE: 150 psi (10.3 bar).</li> <li>MAXIMUM FLUID TEMPERATURE: 140°F (60°C).</li> <li>SPECIFIED FLOWRATE OF 200 gpm (45 m³/hr).</li> <li>FINISH: AS ASSEMBLED.</li> <li>POWER REQUIREMENT: 3/60/460V.</li> <li>NEMA 4X MOTOR STARTER ENCLOSURE WITH SAFETEY DISCONNECT AND H.O.A. SWITCH.</li> </ol>	3/4"[19] TYP	
	<ol> <li>APPROXIMATE DRY WEIGHT: 514 lbs (233 kg).</li> <li>INLET/OUTLET VALVE KIT, MODEL TCV-0200 RECOMMENDED.</li> <li>FLOODED SUCTION REQUIRED.</li> </ol>		11-5/8"[295]
	<u>COMPONENT LIST</u>		21-1/4"[540]-
С	<ol> <li>ELECTRICAL CONTROL BOX: 3/60/460V, W/120V TRANSFORMER.</li> <li>SEPARATOR: ILB-0300.</li> <li>PUMP: 5 HP, CENTRIFUGAL, TEFC, 1750 rpm, 3/60/460V.</li> <li>INLET/OUTLET PRESSURE GAUGES: 0-160 psi, GLYCERIN-FILLED.</li> <li>PURGE EQUIPMENT: SRV-816.</li> <li>DIFFERENTIAL PRESSURE INDICATOR: (AVAILABLE WITH DRY CONTACT MODEL DEC-100. ORDER SEPARATELY.</li> </ol>		(42"[1067]) <u>TOP VIEW</u> (4) (4) (4) (2)
$\rightarrow$		1	
В			
			FRONT VIEW
			SPOOL HIDDEN
A	SYSTEM MODELS		
<b>i</b> 1			

SYSTEM MODELS		
POWER REQUIREMENT	SYSTEM PART NO.	
3/60/208V	187696-208	
3/60/230V	187696-230	
3/60/460V	187696-460	
3/60/575V	187696-575	
OTHER	SEE FACTORY	

4

3

 $\square$ 

 $\checkmark$ 

3

