

4

3

 \square

| | | REVISIONS | - | |
|-----|------|-------------------------|--------------|-----|
| ECN | REV. | DESCRIPTION | DATE APPROVE | |
| | 01 | RELEASE FOR SUBMITTAL | 5/28/15 | JBI |
| | А | RELEASED FOR PRODUCTION | 2/19/22 | TPF |

D

С

 $\overleftarrow{}$

138593

RE/

NOTES:

- 2.
- INLET & OUTLET ARE 8" GROOVED PIPE. MAXIMUM PRESSURE: 150 psi (10.3 bar). MAXIMUM TEMPERATURE: 180°F (82°C). PRESSURE LOSS: 2-15 psid (.14-1.03 bar) AT RATED FLOW. RATED FLOW: 650-1510 gpm (148-343 m³/hr). APPROXIMATE DRY WEIGHT: 1678 lbs (761 kg). FINISH: LAKOS BLACK (EXTERIOR ONLY). 3.
- 4. 5.
- 6. 7.

SUBMITTAL DRAWING

This drawing is submitted for spatial consideration only. Do not pre-plumb to these dimensions.

| UNLESS OTHERWISE SPECIFIED: | | ENGINEERED FOR: | | | \sim – | | | | | |
|---|-------------------------------------|-----------------|------------|-----------|--------------------------------|---|-----------|-------------|------|--|
| DIMENSIONS ARE IN: INCHES [mm] TOLERANCES ARE: | | STANDARD | | | \frown | | $/(\cap$ | | | |
| FRACTIONS | | | | | | | | | | |
| ± 1/2" | DECIMALS ANGLES .XX ± .01 ± 1/4° | | DATE | | 9 – | FILTRATIO | N SOLUTIC | ONS ® | | |
| ,_ | .XXX ± .005 | APPROVALS | DATE | | | | | | | |
| | | DRAWN IDI | E /00 /1 E | TITLE | | | | | | |
| | T SCALE DRAWING | JBI | 5/28/15 | | eHTX-0650-V, SEPARATOR | | | | | |
| MATERIAL | CLASS P-1 | ENGR | | 1 | | | | | | |
| M | NLD CARBON STEEL | - | | | 8" eHTX VERTICAL, CARBON STEEL | | | | | |
| FINISH | | REVIEW | | | | | | | | |
| TINIST | lakos black | - | - | SIZE | MODEL NO. | | DWG NO. | 100500 | REV. | |
| | | WORK ORDER | QTY. | \neg C. | | | | 138593 | A | |
| | | | | SCALE | | /////////////////////////////////////// | EST. WT. | | `` | |
| | | | | SCALE | 1:18 | | 1 | 678 lb 1 OF | 1 | |
| | | | | - | | | | | ı | |
| 2 | | | | | | | | | | |
| | | | 1 | | | | | | | |