


EXCEPT AS OTHERWISE PROVIDED BY CONTRACT, THIS DRAWING AND SPECIFICATIONS SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR MANUFACTURE OR SALE OF MATTER DEPICTED HEREIN WITHOUT THE EXPRESSED WRITTEN PERMISSION OF THE CLAUDE LAVAL CORPORATION, OR ITS ASSIGNEES.


REVISIONS				
ECN	REV.	DESCRIPTION	DATE	APPROVED
	01	RELEASED FOR SUBMITTAL	1/24/19	CEE



- NOTES:
1. INLET & OUTLET ARE 8" GROOVED PIPE.
 2. MAXIMUM PRESSURE: 150 psi (10.3 bar).
 3. MAXIMUM TEMPERATURE: 180°F (82°C).
 4. PRESSURE LOSS: 2-15 psid (.14-1.03 bar) AT RATED FLOW.
 5. RATED FLOW: 650-1510 gpm (148-343 m³/hr).
 6. APPROXIMATE DRY WEIGHT: 1671 lbs (758 kg).
 7. FINISH: LAKOS BLACK (EXTERIOR ONLY).

SUBMITTAL DRAWING

This drawing is submitted for spatial consideration only. Do not pre-plumb to these dimensions.



THIS DRAWING HAS BEEN GENERATED AND IS MAINTAINED BY A CAD SYSTEM. CHANGES SHALL ONLY BE INCORPORATED AS DIRECTED BY AN APPROVED ENGINEERING CHANGE ORDER (ECO). PAPER COPIES ARE UNCONTROLLED.

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN: INCHES (mm) TOLERANCES ARE: FRACTIONS DECIMALS ANGLES ± 1/4" .XX ± .01 ± 1/4° .XXX ± .005 .XXXX ± .0005		ENGINEERED FOR: STANDARD		LAKOS CLAUDE LAVAL CORP. FRESNO, CALIFORNIA 93727 WWW.LAKOS.COM	
DO NOT SCALE DRAWING		APPROVALS	DATE	TITLE	
MATERIAL: CLASS P-1 MILD CARBON STEEL		DRAWN: CEE	1/22/19	eHTX-0650-L, SEPARATOR 650-1510 gpm, CARBON STEEL	
FINISH: LAKOS BLACK		ENGR: -	-	SIZE: C	MODEL NO.
		MFG: -	-	DWG NO. 138594	REV. 01
		WORK ORDER	QTY.	SCALE: 1:16	EST. WT. 1671 lb
				SHEET 1 OF 1	

DWG. NO. 138594 SHEET 1 REV. 01