EXCEPT AS OTHERWISE PROVIDED BY CONTRACT, THIS DRAWING AND SPECIFICATIONS SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR MANUFACTURE OR SALE OF MATTER DEPICTED HEREIN WITHOUT THE EXPRESSED WRITTEN PERMISSION OF THE LAKOS CORPORATION, OR ITS ASSIGNEES.

THIS DRAWING HAS BEEN GENERATED AND IS MAINTAINED BY A CAD SYSTEM. CHANGES SHALL ONLY BE INCORPORATED AS DIRECTED BY AN APPROVED ENGINEERING CHANGE ORDER (ECO). PAPER COPIES ARE UNCONTROLLED.

NOTES:

В

Α

OTHER

Ø 1/2"[13] TYP 1. INLET IS 2" PIPE (NPT). OUTLET IS 1-1/2" PIPE (GROOVED). 2. D PURGE OUTLET IS 3/4" NPT. 3. MAXIMUM PRESSURE: 150 psi (10.3 bar). 4. 3/4"[19] TYP-MAXIMUM FLUID TEMPERATURE: 140°F (60°C). 5. SPECIFIED FLOWRATE OF 65 gpm (15 m<sup>3</sup>/hr). 6. FINISH: AS ASSEMBLED. 7. POWER REQUIREMENT: 3/60/460V. 8. 9. NEMA 4X MOTOR STARTER ENCLOSURE WITH SAFETEY DISCONNECT AND H.O.A. SWITCH. 10. APPROXIMATE DRY WEIGHT: 390 lbs (177 kg). 11. INLET/OUTLET VALVE KIT, MODEL TCV-0065 RECOMMENDED. 12. MINIMUM PIPE FROM TOWER BASIN TO TC SYSTEM IS 2-1/2" PIPE. 13. FLOODED SUCTION REQUIRED. 8-7/16"[214] -<u>COMPONENT LIS</u>T —19-7/8"[506] ELECTRICAL CONTROL BOX: 3/60/460V, W/120V TRANSFORMER. (1)- (41"[1041]) (2)SEPARATOR: ILB-0150. C  $\overline{(3)}$ PUMP: 3 HP, CENTRIFUGAL, TEFC, 3500 rpm, 3/60/460V. TOP VIEW (4)INLET/OUTLET PRESSURE GAUGES: 0-160 psi, GLYCERIN-FILLED. 5 PURGE EQUIPMENT: SRV-816. (6)DIFFERENTIAL PRESSURE INDICATOR: (AVAILABLE WITH DRY CONTACT MODEL DEC-100. ORDER SEPARATELY). (7)BASKET STRAINER. P 5(6)FRONT VIEW STRAINER HIDDEN SYSTEM MODELS POWER REQUIREMENT SYSTEM PART NO. 187687-208 3/60/208V 187687-230 3/60/230V 187687-460 3/60/460V 3/60/575V 187687-575

SEE FACTORY

4

 $\square$ 

3

 $\overline{}$ 

